## **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/20111 amended by Commissions delegated Regulation (EU) No 574/2014 **No 650** 

1. Unique identification code of the product-type: MARISEAL 650

2. Intended use: Liquid-applied water impermeable product, type RM for

installations on walls and floors, beneath ceramic tiling (bonded

with C2 adhesive in accordance with EN 12004)

3. Manufacturer: MARIS POLYMERS S.A.

**Industrial Area of Inofita** 

GR-32011 Inofita

Greece

4. Authorised representative: Not relevant

5. System of assessment and verification of

constancy of performance:

System 3

6. Harmonised standard: EN 14891: 2012/AC: 2013

Liquid-applied water impermeable products for use beneath ceramic tiling bonded with adhesives - Requirements, test methods, evaluation of conformity, classification and

designation.

Notified body: No. 1301

TECHNICKÝ A SKÚŠOBNÝ ÚSTAV STAVEBNÝ, n. o. Studená 3, 821 04 Bratislava, Slovak Republic

## 7. Declared performances:

Essential characteristics	Performance	Test standard	Harmonized technical specification
Initial tensile adhesion strength	≥ 0,5 N/mm <sup>2</sup>	EN 14891, Clause A6.2	
Waterproofing	No penetration	EN 14891, Clause A.7	EN 14891: 2012 /AC: 2012
Crack bridging ability under standard conditions	≥ 0,75 mm	EN 14891, Clause A.8.2	
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm²	EN 14891, Clause A6.5	
Tensile adhesion strength after water contact	≥ 0,5 N/mm²	EN 14891, Clause A6.4	
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm²	EN 14891, Clause A6.9	
Tensile adhesion strength after freeze- thaw cycles	≥ 0,5 N/mm²	EN 14891, Clause A6.6	
Release dangerous substances	see MSDS	-	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: MARIS POLYMERS SA